

Threaded Drop Pipe

PVC pipe



ASTM D1785
ASTM D1784 Cell Class 12454
ANSI/NSF 14 Uniform Plumbing code

1700 S. Lincoln St., Siloam Springs, AR 72761

Markets



Potable



Irrigation

Description

Available Pipe Sizes

Sch.80 3/4", 1", 1-1/4", 1-1/2", 2"

Sch.120 1", 1-1/4", 1-1/2", 2"

Pipe Joint Length = 20 feet

Available Colors

White

- > Manufactured from 1120-1220 PVC - bears NFS Seal of Certification
- > The smooth interior improves flow characteristics, cuts friction loss.
- > Light weight - approximately one-fourth the weight of schedule 40 Iron pipe
- > Easy to install-furnished in 20' lengths with thread protectors on each end, or with coupling and thread protector.
- > Not subject to rust, corrosion or electrolytic deterioration - many years of longevity.
- > More economical than alternate materials.
- > Use a torque arrestor over 150"

Sch80 Threaded - ASTM D-1785

PVC Threaded Drop Pipe (Threaded both ends)

Size	Average OD	Nominal ID	Min Wall	Max PSI 73.4F	Max Depth	Max HP	Weigh per foot	Pallet footage	order units	FT Truck
3/4"	1.050	0.736	0.154	350	610 feet	1.5	0.279	5400	1	
1"	1.315	0.937	0.179	315	610 feet	1.5	0.411	4000	1	
1-1/4"	1.660	1.256	0.191	260	475 feet	2.0	0.568	2760	1	
1-1/2"	1.900	1.486	0.200	235	435 feet	5.0	0.688	1880	1	
2"	2.375	1.913	0.218	200	350 feet	7.5	0.952	2800	1	

Sch120 Threaded - ASTM D-1785

PVC Threaded Drop Pipe (Threaded both ends)

Size	Average OD	Nominal ID	Min Wall	Max PSI 73.4F	Max Depth	Max HP	Weigh per foot	Pallet footage	order units	FT Truck
1"	1.315	0.891	0.200	360	600 feet	1.5	0.450	4000	1	
1-1/4"	1.660	1.204	0.215	300	500 feet	2.0	0.628	2760	1	
1-1/2"	1.900	1.424	0.225	270	450 feet	5.0	0.762	1880	1	
2"	2.375	1.845	0.250	240	375 feet	7.5	1.075	2800	1	



This Information may have updates. Please visit: jetstreampipes.com for all updated information.

Customer Service 1-800-643-3470

THIS PRODUCT IS MADE IN AMERICA

Printed 2021